



The Zodiac TRi-XO Series features everything you have come to expect from the leaders in water care products, plus the added benefit of now being able to 'CrossOver' from using traditional salt chlorination to also mineral chlorination.

Eco Conscious

Helps reduce additional chemical use







The Zodiac TRi-XO CrossOver provides great flexibility and performance. With inbuilt software that has been designed to configure to either traditional salt chlorination or CrossOver to using mineral salts. You can CrossOver at anytime, so even if you begin using salt you can reset the software and reconfigure to use minerals.

TRi-XO was designed in Australia to take on the harsh climate and environment of the pool area and provide great reliability year after year. It is packed with features to make looking after your pool easier and more affordable, plus choose salt or minerals to suit your preference.

Outstanding Features

- A simple to use control interface makes setting up a breeze, includes built in timers and help menu
- Long life Reverse Polarity electrode plates for increase cell life and decreased maintenance
- Boost mode to handle the really hot days or when you need a little extra for the pool party
- Low/Spa Mode makes it ideal for pool/spa combo pools and if you're using a blanket
- 40 and 50mm plumbing ports make it suitable for new or retrofit applications

Enhance your bathing experience

Zodiac recommends using TRi-XO with our mineral salt called ElementTM. This is a magnesium rich salt blend making your bathing experience more enjoyable. In some cases it may be necessary at the start up to use ElementTM Activate mineral salts. Seek advice from your pool care professional about converting your pool.

Warranty

For Product warranty registration & information on warranty details:

For Australia: visit www.zodiac.com.au/warranty For New Zealand: visit www.zodiac.co.nz/warranty

Perfect to use with Zodiac Element™ Mineral Salts





Specifications

DESCRIPTION	TRI-XO COMPACT	TRI-XO MID	TRI-XO LARGE
MAXIMUM* AVERAGE POOL SIZE (LITRES)	40,000	70,000	100,000
SALT OR MINERALS	SUITABLE FOR BOTH		
PLUMBING	40MM OR 50MM		
RECOMMENDED OPERATING SALINITY	4,000PPM		
SALINITY RANGE	3,500PPM - 10,000 PPM		
POWERPACK DIMENSIONS (HWD)	330MM X 310MM X 110MM		
CELL DIMENSIONS (HWD)	320MM X 155MM X 110MM		

^{*}Based on a warm weather climate. Adjust for cooler or hotter climates.

